



## MOUNTING SUGGESTIONS:

### Harley-Davidson® Dyna 2006-2017 One-piece Seat

<b>Hardware:</b>	Stock fender screw
<b>Tools needed:</b>	Phillips screwdriver

#### **Removal of stock seat:**

*One-piece stock seat:*

1. Remove the rear 1/4"-20 fender screw with a Phillips screwdriver and set it aside. The stock rear fender screw will be used to attach your new Mustang seat.
2. Remove the handstrap if present.
3. Slide the seat up and back to disengage the front bracket and remove the seat.
4. Remove any rubber bumpers or handstrap bolts from the fender. These are not needed to mount your Mustang seat.



#### **Installation of Mustang seat:**

1. Insert nose tab into frame mount under tank.
2. Align rear bracket with fender nut and secure the bracket to the fender with the stock screw.

Enjoy the comfort and custom look of your new Mustang seat!



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392 or 413-668-1100, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to [questions@mustangseats.com](mailto:questions@mustangseats.com) or visit our website at [www.mustangseats.com](http://www.mustangseats.com).

For care and maintenance of our seats, please go to our website under "Support".

Refers to part numbers: 75435, 75480, 75535, 75545, 75595, 75605, 75615, 75625, 75639, 76059, 76770

**You are cordially invited to  
— Tour the Mustang Factory —**

See how our craftspeople take pride in transforming raw materials into the world's highest quality, most comfortable handcrafted seats. Please contact Mustang for more information regarding tours of our historic Three Rivers, Massachusetts, facility (only 75 miles west of Boston; 150 miles northeast of New York City). Our two hour tours are by reservation only; we can accommodate groups from 2 to 24. We promise you will ride away with an entirely new awareness of what you put between you and your bike.