

Deluxe Rack Bag TR3300DE



17801 S. Susana Rd.
Rancho Dominguez, CA 90221
(310) 638-1222 Fax (310) 761-1234
www.saddlemen.com

⚠ WARNING

READ ALL INSTRUCTIONS THOROUGHLY BEFORE STARTING!

You are responsible for the correct installation and safe use of this bag. Seek qualified instruction if you are uncertain about its capabilities and limitations or if you need help with installation. Use of the bag in a manner other than its intended purpose or contradictory to the warnings and instruction provided could cause loss of control of your motorcycle, possibly resulting in personal injury or death.

" Do not use this bag if any part of the mounting system has deteriorated, loosened or is beginning to fail. If you have any doubts as to the security of bag's installation, stop using it.

" After every stop check the bag to be certain that it did not shift while riding and verify that the straps will not contact or interfere with any part of the drivetrain, suspension, brakes or wheels.

" Do not exceed 20 pounds total weight of bag, contents and attachments or the load limits of the motorcycle as specified in the owner's manual supplied with the bike or from the bike manufacturer.

" When the bag is removed, all loose straps must be removed from the motorcycle, or secured, so that they do not contact or interfere with any part of the drivetrain, suspension, brakes or wheels before operating the motorcycle.

" Always remove or stow all shoulder and backpack straps before attaching bag to motorcycle.

If you do not understand these instructions, the warning label attached inside the bag or how to safely and securely mount this bag, please **SEEK PROFESSIONAL HELP** at your qualified motorcycle dealer or by calling SADDLEMEN at 310-638-1222

Motorcycling is an inherently dangerous activity. Installation of any accessory, including this bag, can add to the danger if it is not installed safely. You must install this product in a manner in which it will not contact any part of the drivetrain, suspension or steering, or interfere with any operation of the motorcycle. If you do not know how to do this, or have any doubts as to your ability, please see a qualified motorcycle mechanic.

INSTALLATION INSTRUCTIONS

1. There are 3 straps near the bottom of the bag, two in front and one in back. These straps are secured to the bag. For each strap, undo the buckle, remove the strap, and wrap the strap around a rail of your luggage rack, then secure the strap back into the buckle, and tighten.
2. Each bag also includes two quick-release nylon straps. These straps must clip into the D-Ring on each side of the bag, and wrap around a secure, solid part of the motorcycle like a saddlebag support, frame rail, etc.

NOTE: DO NOT connect any straps to flexible or moving parts (rubber mounted turn signals or handlebars)

NOTE: You must tuck away, tie, or cut/shorten all loose mounting straps that might interfere with operation BEFORE you ride the motorcycle. See warning information above.

NOTE: Check bag mounting strap tightness each time you stop.

CARE AND CLEANING

Your Saddlemen bag require almost no maintenance, but to keep them looking their best, we recommend Saddlemen's Ultra wash Cleaner #3101, and Fabric Conditioner #3103. For everyday cleaning, you can simply wipe down the bag with a clean, damp cloth.

SADDLEMEN'S ONE-YEAR WARRANTY

We guarantee our products for a period of one year after retail purchase, against defects in materials and workmanship. Damage caused by improper use or incorrect mounting is not warranted. Our warranty has other provisions and conditions; please contact Saddlemen for full details. If your Saddlemen product is not performing to your expectations, please call us directly and our customer service staff will be happy to help. You can count on Saddlemen's quality, innovation, service and style. If your Saddlemen product is not performing to your expectations, please call us directly and our customer service staff will be happy to help. You can count on Saddlemen's quality, innovation, service and style.



Make sure each of the three strap cam locks is positioned the correct direction so it cannot loosen after installation.

